

Material Safety Data Sheet

CS: 1.4.51

Page: 1 of 4

Infosafe No™ LPSDZ

Issue Date : July 2009

ISSUED by SLIMESOU

Product Name **SLIME SUPER DUTY TIRE SEALANT**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name SLIME SUPER DUTY TIRE SEALANT
Company Name Slime South Pacific PTY LTD.
Address 39 Pinnacle Cres Flagstaff Hill
South Australia 5159 Australia
Emergency Tel. 08 8270 1011
Telephone/Fax Number Tel: 08 8296 4722
Fax: 08 8296 4122
Recommended Use Sealant.

2. HAZARDS IDENTIFICATION

Hazard Classification Not classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia.
Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).
Safety Phrase(s) S24/25 Avoid contact with skin and eyes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Information on Composition Paste contains 1,2-Propylene glycol.

Ingredients	Name	CAS	Proportion
	Ingredients determined not to be hazardous		100 %

4. FIRST AID MEASURES

Inhalation Remove affected person from exposure. Allow to assume most comfortable position and keep warm. Keep at rest until fully recovered. If symptoms persist seek medical attention.
Ingestion Do not induce vomiting. Rinse mouth and lips thoroughly with water. Seek medical attention.
Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation develops seek medical attention.
Eye If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed off completely. Seek medical attention.
First Aid Facilities Eye wash station and normal washroom facilities.
Advice to Doctor Treat symptomatically.
Other Information For advice in an emergency, contact a Poisons Information Centre (Phone in Australia 13 11 26) or a doctor.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media Foam, dry chemical powder, carbon dioxide, water fog or water spray.
Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and hydrocarbons.
Specific Hazards The product is not combustible, but under fire conditions, the components may decompose and/or burn.
Decomposition Temp. Not available
Precautions in connection with Fire Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) and full protective clothing to prevent exposure to vapours, fumes or products of combustion. Water spray may be used to cool down heat-exposed containers.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures Wear protective clothing and equipment to prevent exposure. The floors may be slippery. Remove unprotected personnel. If possible contain the spill. Place

Material Safety Data Sheet

CS: 1.4.51

Page: 2 of 4

Infosafe No™ LPSDZ

Issue Date : July 2009

ISSUED by SLIMESOU

Product Name **SLIME SUPER DUTY TIRE SEALANT**

inert absorbent such as sand onto material. Prevent run off into drains and waterways. Collect the material and place into suitable, labelled containers. If contamination of sewers or waterways occurs inform the local water authorities and EPA in accordance with local regulations. Dispose of waste according to applicable local and national regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling	Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use only in well ventilated areas. Avoid breathing vapour or spray mist. Keep containers closed when not in use. Do not empty into drains. Maintain a high level of personal hygiene when using the product, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities.
Conditions for Safe Storage	Store in a cool, dry, well ventilated area away from oxidising agents and acids. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards	No exposure standards have been established for the mixture by the National Occupational Health & Safety Commission (NOHSC), Australia. However, over-exposure to some chemicals may result in adverse effects on health or enhancement of pre-existing medical conditions and/or allergic reactions and should be kept to the lowest possible levels.
Engineering Controls	Provide sufficient ventilation to keep airborne levels as low as possible. Where natural ventilation is inadequate, and vapours or mists are generated, a local exhaust ventilation system, drawing vapours/mists away from workers' breathing zone, is required.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a particulate/mist filter should be used. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
Eye Protection	Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear laminated film, nitrile, neoprene or other suitable, impervious gloves. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Green paste with black specks, slight odour.
Decomposition Temperature	Not available
Melting Point	Not available
Boiling Point	104.4°C
Solubility in Water	Soluble
Specific Gravity	1.05 +/- 0.05
pH Value	7.8-9.8
Vapour Pressure	Not available
Vapour Density (Air=1)	>1
Evaporation Rate	<1 (n-Butyl acetate=1)

Material Safety Data Sheet

CS: 1.4.51

Page: 3 of 4

Infosafe No™ LPSPDZ

Issue Date : July 2009

ISSUED by SLIMESOU

Product Name **SLIME SUPER DUTY TIRE SEALANT**

Viscosity	Not available
Flash Point	Not applicable
Flammability	Non-combustible liquid.
Auto-Ignition Temperature	Not applicable
Flammable Limits - Lower	Not applicable
Flammable Limits - Upper	Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions of storage and handling.
Incompatible Materials	Strong oxidising agents and strong acids.
Hazardous Decomposition Products	Thermal decomposition products include hydrocarbons, carbon monoxide and carbon dioxide.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information	Not available
Inhalation	Vapours or spray mist may be irritating to the respiratory system.
Ingestion	Ingestion of this product may irritate the gastric tract, causing nausea and vomiting.
Skin	Repeated or prolonged exposure may be irritating to skin.
Eye	May be irritating to eyes. May cause stinging, redness and tearing of the eyes.
Chronic Effects	Not available

12. ECOLOGICAL INFORMATION

Ecotoxicity	Not available
Persistence / Degradability	Not available
Mobility	Not available
Bioaccumulative Potential	Not available
Environ. Protection	Do not discharge the product into drains, waterways or sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.
--------------------------------	--

14. TRANSPORT INFORMATION

Transport Information	Road and Rail Transport (ADG Code): Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code). Marine Transport (IMO/IMDG): Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. Air Transport (ICAO/IATA): Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
------------------------------	--

Material Safety Data Sheet

CS: 1.4.51

Page: 4 of 4

Infosafe No™ LPSDZ Issue Date : July 2009 ISSUED by SLIMESOU

Product Name **SLIME SUPER DUTY TIRE SEALANT**

15. REGULATORY INFORMATION

Regulatory Information Not classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia.
Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

Poisons Schedule Not Scheduled

AICS (Australia) All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Date of preparation or last revision of MSDS MSDS Reviewed: July 2009
Supersedes: May 2004

Contact Person/Point Michael Cooper
Emergency contact number : 08 8270 1011
...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.